1983 Subject and Author Index

All of the articles in the 1983 Forest Products Journal, Volume 33, are listed both by subject and by author. The Subject Index is organized according to the FPRS Division and Technical Committee structure.

The Author Index lists senior author entries which give complete information for the article, and coauthor entries which refer back to the senior author.

Reprints of most articles are available at $2 each, minimum $5, plus 10 percent shipping and handling. Bulk rates are also available. When ordering, please give reprint numbers. A check or money order must accompany each order.

FUNDAMENTAL DISCIPLINES DIVISION

Biology

An Australian Test for Decay in Painted Timbers Exposed to the Weather, J. Beesley, J.W. Creffield, and I.W. Saunders, 5:57-63 (No. 6472).

Bacterial Oak: Drying Problems, J.C. Ward and D.A. Groom, 10:57-65 (No. 6427).

Biodeterioration and Strength Reductions in Preservative Treated Aspen Waferboard, E.L. Schmidt, H. J. Hall, R.O. Gertjejansen, C.G. Carll, and R.C. DeGroot, 11/12:45-53 (No. 6570).

Chemical Brown Staining of Douglas-fir Sapwood, D.J. Miller, D.M. Knutson, and R.D. Tocher, 4: 44-48 (No. 6481).

Decay in Mine Timbers. Part I. Sampling Procedures and Conditions and Descriptions of Samples, W.E. Eslyn, 6:27-30 (No. 6534).

Decay in Mine Timbers. Part II. Basidiomycetes Associated With Decay of Coal Mine Timbers, W.E. Eslyn and F.F. Lombard, 7/8:19-23 (No. 6535).

Decay Resistance of Alaska-cedar, T.C. Scheffer, 1:25-26 (No. 6241).

An Investigation of the Natural Resistance of Melaleuca quinquenervia to Tropical and Terrestrial Wood-Destroying Organisms, J.D. Bultman, R.H. Beal, J.B. Huffman, and K.K. Parrish, 3:39-43 (No. 6471).

Laboratory Evaluation of Selected Fungicides for Control of Sapstain and Mold on Southern Pine Lumber, W.E. Eslyn and D.L. Cassens, 4:65-68 (No. 6510).

Natural Decay Resistance of the Heartwood of Coast Redwood Sequoia Sempervirens (D. Don) Endl., J.W. Clark and T.C. Scheffer, 5:15-20 (No. 6240).

Properties of Hardboards Made From Tropical Hardwoods and Aspen Chips Before and After Simulated Outdoor Storage, G.C. Myers, 2:39-42 (No. 6439).

Relationship Between Early Decay and Radial Compression Strength of Douglas-fir, S.M. Smith and R.D. Graham, 6:49-52 (No. 6514).

Sensitivity of the "Pick Test" for Field Detection of Early Wood Decay, W.W. Wilcox, 2:29-30 (No. 6490).

Serviceability of Douglas-fir Shakes After 22 Years on a Roof in Western Oregon, D.J. Miller, 11/12:66-68 (No. 6561).

A Slide-Hammer for Pulling Plugs in Fumigated Transmission Poles, G.M. Cantara and R.D. Graham, 5:45 (No. 6543).

Stem Characteristic Changes Affect Long-Term Planning for Timber Resources Utilization, P.F. Ffolliott, W.O. Rasmussen, and G.J. Gottfried, 2:57-60 (No. 6476).

Wood Properties of Immature Ponderosa Pine After Thinning, D.C. Markstrom, H.E. Troxell, and C.E. Boldt, 4:33-36 (No. 6503).

Chemistry

Assessment of the 2-Hour Desiccator Test for Formaldehyde Release From Particleboard, J. Rybicky, K. Horst, and S.M. Kambanis, 9:50-54 (No. 6527).

Effect of Accelerated Fixation on Decay of CCA-Treated Wood, A.F. Preston and P.A. McKaig, 11/12:41-44 (No. 6553).

Formaldehyde Emission From Particleboard and Plywood Paneling: Measurement, Mechanism, and Product Standards, G.E. Myers, 5:27-37 (No. 6492).

Use of Acid Scavengers to Improve Durability of Acid-Catalyzed Adhesive Wood Bonds, G.E. Myers, 4:49-57 (No. 6464).

Physics

Effects of Outside Storage on the Energy Potential of Hardwood Particulate Fuels: Part I. Moisture Content and Temperature, M.S. White, M.L. Curtis, R.L. Sarles, and D.W. Green, 6:31-38 (No. 6521).

Effects of Outside Storage on the Energy Potential of Hardwood Particulate Fuels: Part II. Higher and Net Heating Values, M.S. White, M.L. Curtis, R.L. Sarles, and D.W. Green, 11/12:61-65 (No. 6522).

Longitudinal Moisture Response in Truss Lumber—A Potential Cause of Ceiling-Partition or Floor-Partition Separation, D.H. Percival and S.K. Suddarth, 11/12:19-28 (No. 6557).

Moisture Changes in Oak and Hickory Fuel Chips on Roofed and Unroofed Louisiana Air-Drying Grounds as Affected by Pile Depth and Turning of Chips, P. Koch, 6:59-61 (No. 6533).

Surface Roughness of Wood-Based Panels After Aging, B. A-L. Ostman, 7/8:35-42 (No. 6457).

Wood/Bark Adhesion Measurements Assist in Drum Debarker Development, D.W. Einspahr and M.L. Harder, 5:21 (No. 6552).

Wood Engineering & Mechanical Properties

Biodeterioration and Strength Reductions in Preservative Treated Aspen Waferboard, E.L. Schmidt, H.J. Hall, R.O. Gertjejansen, C.G. Carll, and R.C. DeGroot, 11/12:45-53 (No. 6570).

Compression Perpendicular to the Grain in Dry Douglas-fir and Hem-fir, J.W. Johnson, 3:55-63 (No. 6474).

Effect of Delay Between Treatment and Drying on Toughness of CCA-Treated Southern Pine, J.E. Winandy, B.A. Bendtsen, and R.S. Boone, 6:53-58 (No. 6520).

Effect of High-Temperature Drying on Bending Strength of Yellow-poplar 2 by 4's, C.C. Gerhards, 2:61-67 (No. 6465).

Effect of Shives Content on Hardboard Properties, Y. DeXin and B. Ostman, 3:26-30 (No. 6479).

Effects of Accelerated Aging Tests on Some Bending Properties of Hardwood Composite Panels, P. Chow and J.J. Janowiak, 2:14-20 (No. 6460).

Hardboard Stiffness and Tensile Strength Over a Moisture and Temperature Range Simulating Exterior Use, E.L. Back and B. A-L. Ostman, 6:62-68 (No. 6519).

Hardness of Douglas-fir and Ponderosa Pine Treated With ACA, CCA, and Penta-Petroleum, J.D. Lew and W.A. Dost, 7/8:17-18 (No. 6524).

Longitudinal Moisture Response in Truss Lumber—A Potential Cause of Ceiling-Partition or Floor-Partition Separation, D.H. Percival and S.K. Suddarth, 11/12:19-28 (No. 6557).

Mechanical Properties of Conventionally Kiln-Dried and Pressure Steam-Dried Yellow-poplar and Red Oak, H.N. Rosen and S.E. Laurie, 1:50-52 (No. 6468).

Predicting the Bending Strength of Ladder Rail Stock, M.A. Dean and A.J. Kass, 9:9-16 (No. 6525).

Proof Test Load Value Determination for Maximum Economic Return, F.K. Bechtel, 10:30-38 (No. 6470).

Properties of Hardboards Made From Tropical Hardwoods and Aspen Chips Before and After Simulated Outdoor Storage, G.C. Myers, 2:39-42 (No. 6439).

Properties of 1/2-Inch Composite Plywood With Southern Yellow Pine Veneer Faces and Unidirectionally Oriented Southern Oaks Strand Core, E.J. Biblis and F. Mangalousis, 2:43-49 (No. 6447).

Relationship Between Early Decay and Radial Compression Strength of Douglas-fir, S.M. Smith and R.D. Graham, 6:49-52 (No. 6514).

Relationship of Bending Strength to Stiffness of Yellow-poplar 2 by 4's, C.B. Koch, 6:17-20 (No. 6248).

Relationship of Fiber Preparation and Characteristics to Performance of Medium-Density Hardboards, G.C. Myers, 10:43-51 (No. 6518).

Strength and Stiffness of Clear Douglas-fir Exposed to the Mount St. Helens Volcanic Eruption, H. Resch, J.W. Johnson, and B.A. Bendtsen, 7/8:52-56 (No. 6484).

Toughness of Healthy and Spruce Budworm-Killed Balsam Fir, S.A. Sinclair and D.P. Barnes, 7/8:24-26 (No. 6515).

Wood Properties of Immature Ponderosa Pine After Thinning, D.C. Markstrom, H.E. Troxell, and C.E. Boldt, 4:33-36 (No. 6503).

Ultimate Strength of Structural Particleboard Diaphragms, G.H. Atherton, 5:22-26 (No. 6501).

MANAGEMENT

Economics & Financial Management

Comparing In-Place Costs of Wood and Masonry Foundations, H. Spelter, 9:45-49 (No. 6547).

Cost Comparison of Two Processes for Laminating Thick Veneer, S.P. Loehnertz, 11/12:57-60 (No. 6563).

Economics of Manufacturing Structural Lumber From Hardwoods Using the Saw-Dry-Rip (SDR) Concept, G.B. Harpole, 6:39-42 (No. 6500).

A Financial Analysis of Furniture Parts From Short Bolts, H.A. Huber, H.N. Rosen, H.A. Stewart, and S.B. Harsh, 9:55-58 (No. 6433).

How Export Promotion Programs Influence Trade, D.R. Darr, 4:15-20 (No. 6480).

A Method for Estimating the Multi-Product Value of Hardwood Timber Stands, C.R. Blinn, S.A. Sinclair, and A.R. Ek, 3:49-54 (No. 6485).

Marketing

Forest Products in the Future: The Eighties as Prologue, J.A. Ball, 10:9-13 (No. 6627).

How Export Promotion Programs Influence Trade, D.R. Darr, 4:15-20 (No. 6480).

Production Management

An Analytic Approach to Estimating the Increase in Lumber Recovery Due to Reduced Target Sizes and Saw Kerfs, S.J. Wang, 11/12:29-32 (No. 6564).

Derived Demand of Factors of Production in the Pulp and Paper Industry, F. Sherif, 1:45-49 (No. 6306).

Effect of Gang-Ripping Width on C1F Yields From No. 2 Common Oak Lumber, C.J. Gatchell, R.B. Anderson, and P.A. Araman, 6:43-48 (No. 6539).

Lumber Grade Yields From Spruce Budworm-Damaged Balsam Fir, R.L. Govett, S.A. Sinclair, and J.L. Bowyer, 5:46-50 (No. 6498).

Proof Test Load Value Determination for Maximum Economic Return, F.K. Bechtel, 10:30-38 (No. 6470).

Simulated Effects of Productivity Rates, Input Costs, and Stand Volumes on Harvesting Costs, F.W. Cubbage, 2:50-56 (No. 6461).

Veneer Recovery From Live and Dead Lodgepole Pine, T.A. Snellgrove and S. Ernst, 6:21-26 (No. 6537).

Quality Control

Comparison of Wet and Dry Desiccator Test Methods for Formaldehyde Emission From UF-Bonded Wood Products, B. Meyer, K. Koshlap, K.L. Geisling, and R.R. Miksch, 1:35-37 (No. 6466).

Hot Melt Adhesive Applicator Speeds Gluing of Internal Bond Test Specimens, G.A. Lebens and H.J. Hall, 7/8:33-34 (No. 6560).

The Minnesota Shear Test, H.J. Hall and J.R. Haygreen, 9:29-32 (No. 6559).

Sensitivity of the "Pick Test" for Field Detection of Early Wood Decay, W.W. Wilcox, 2:29-30 (No. 6490).

Research Management

Forest Products in the Future: The Eighties as Prologue, J.A. Ball, 10:9-13 (No. 6627).

Forest Service Research--New Views of an Old Mission, R.L. Youngs, 11/12:15-18 (No. 6623).

PROCESSES DIVISION

Drying & Storage

Bacterial Oak: Drying Problems, J.C. Ward and D.A. Groom, 10:57-65 (No. 6427).

Drying Sweetgum Veneer With Various Combinations of Impinging Hot Air and Microwave Energy, J.R. Olson and D.G. Arganbright, 5:51-56 (No. 6303).

Economics of Manufacturing Structural Lumber From Hardwoods Using the Saw-Dry-Rip (SDR) Concept, G.B. Harpole, 6:39-42 (No. 6500).

Effect of High-Temperature Drying on Bending Strength of Yellow-poplar 2 by 4's, C.C. Gerhards, 2:61-67 (No. 6465).

Gluability of Platen-Dried Veneer of Douglas-fir, M.D. Sandoe, J.D. Wellons, R.J. Parker, and R. Jokerst, 7/8:57-62 (No. 6455).

Manufacture of Quality Yellow-poplar Studs Using the Saw-Dry-Rip Concept, R.R. Maeglin and R.S. Boone, 3:10-18 (No. 6477).

Mechanical Properties of Conventionally Kiln-Dried and Pressure Steam-Dried Yellow-poplar and Red Oak, H.N. Rosen and S.E. Laurie, 1:50-52 (No. 6468).

Pressure Steam Drying of Lumber, H.N. Rosen, R.E. Bodkin, and K.D. Gaddis, 1:17-24 (No. 6450).

Energy Generation & Conservation

Effects of Outside Storage on the Energy Potential of Hardwood Particulate Fuels: Part I. Moisture Content and Temperature, M.S. White, M.L. Curtis, R.L. Sarles, and D.W. Green, 6:31-38 (No. 6521).

Effects of Outside Storage on the Energy Potential of Hardwood Particulate Fuels: Part II. Higher and Net Heating Values, M.S. White, M.L. Curtis, R.L. Sarles, and D.W. Green, 11/12:61-65 (No. 6522).

Moisture Changes in Oak and Hickory Fuel Chips on Roofed and Unroofed Louisiana Air-Drying Grounds as Affected by Pile Depth and Turning of Chips, P. Koch, 6:59-61 (No. 6533).

Pickup Trucks as Units for Measuring Firewood, A.P.C. Marsinko and T.E. Wooten, 1:43-44 (No. 6482).

Screening Biomass Species for Methane Production in Florida: Description of a Research Program, S-c. Wang, 10:66-68 (No. 6523).

Wood Energy Use in the Lumber and Wood Products Industry, A. Goetzl and S. Tatum, 3:44-48 (No. 6511).

Wood-Fired Steam Production--A Case Study, F-B. Lin, 7/8:63-69 (No. 6526).

Finishing & Overlaying

An Australian Test for Decay in Painted Timbers Exposed to the Weather, J. Beesley, J.W. Creffield, and I.W. Saunders, 5:57-63 (No. 6472).

Gluing

Bond Formation by Wood Surface Reactions: Part III--Parameters Affecting the Bond Strength of Solid Wood Panels, S.S. Kelley, R.A. Young, R.M. Rammon, and R.H. Gillespie, 2:21-28 (No. 6463).

Comparison of Wet and Dry Desiccator Test Methods for Formaldehyde Emission From UF-Bonded Wood Products, B. Meyer, K. Koshlap, K.L. Geisling, and R.R. Miksch, 1:35-37 (No. 6466).

Edge-Gluing Unseasoned Spruce-Pine-Fir Lumber Using a Preheating Method, G.E. Troughton and R.C. Casilla, 5:38-44 (No. 6496).

Gluability of Platen-Dried Veneer of Douglas-fir, M.D. Sandoe, J.D. Wellons, R.J. Parker, and R. Jokerst, 7/8:57-62 (No. 6455).

Hot Melt Adhesive Applicator Speeds Gluing of Internal Bond Test Specimens, G.A. Lebens and H.J. Hall, 7/8:33-34 (No. 6560).

Use of Acid Scavengers to Improve Durability of Acid-Catalyzed Adhesive Wood Bonds, G.E. Myers, 4:49-57 (No. 6464).

Mechanical Fastening

Influence of Flange Quality on the Load-Carrying Capacity of Composite Webbed I-Beams in Flexure, M. Samson, 1:38-42 (No. 6453).

Milling & Machining

An Analytic Approach to Estimating the Increase in Lumber Recovery Due to Reduced Target Sizes and Saw Kerfs, S.J. Wang, 11/12:29-32 (No. 6564).

Chunkwood Production: A New Concept, R.A. Arola, S.A. Winsauer, R.C. Radcliffe, and M.R. Smith, 7/8:43-51 (No. 6508).

Cutting Forces and Surface and Flake Quality From Face-Milling Combinations, H.A. Stewart, 7/8:27-32 (No. 6396).

Economics of Manufacturing Structural Lumber From Hardwoods Using the Saw-Dry-Rip (SDR) Concept, G.B. Harpole, 6:39-42 (No. 6500).

Effect of Gang-Ripping Width on C1F Yields From No. 2 Common Oak Lumber, C.J. Gatchell, R.B. Anderson, and P.A. Araman, 6:43-48 (No. 6539).

Manufacture of Quality Yellow-poplar Studs Using the Saw-Dry-Rip Concept, R.R. Maeglin and R.S. Boone, 3:10-18 (No. 6477).

The Mechanics of Auger Cutters for Wood, J.A. Mattson, 2:31-38 (No. 6451).

Performance Tests on the Powered Back-Up Roll, J. Edens, 1:53-61 (No. 6459).

Performance of a Thin Circular Headsaw Cutting Hardwoods, D.G. Cuppett, 9:33-35 (No. 6556).

Proportion of Northern Red Oak Veneer Logs Processed Into Veneer and Byproducts in a Half-Round Slicing Operation, E.D. Rast, 11/12:54-56 (No. 6577).

SPSM--A Southern Pine Sawmill Model, F.G. Wagner, Jr., and F.W. Taylor, 4:37-43 (No. 6505).

Wood/Bark Adhesion Measurements Assist in Drum Debarker Development, D.W. Einspahr and M.L. Harder, 5:21 (No. 6552).

Timber Production & Harvesting

Chunkwood Production: A New Concept, R.A. Arola, S.A. Winsauer, R.C. Radcliffe, and M.R. Smith, 7/8:43-51 (No. 6508).

Cubic Log Scale Deductions in Dead Timber: An Empirical Approach, J.M. Cahill, 4:21-24 (No. 6494).

Features of a Felling Module Using a Feller-Buncher in a Timber Harvesting Computer Simulation Model, D.B. Webster, M.L. Padgett, and D.L. Sirois, 6:11-16 (No. 6506).

Features of a Skidding Module in a Timber Harvesting Computer Simulation Model, G.S. Hines, C-Y. Liu, D.B. Webster, and D.L. Sirois, 7/8:11-16 (No. 6507).

Handling the Small Tree Resource With Cable Systems, L.D. Kellogg, 4:25-32 (No. 6509).

Harvesting Developments for Short Rotation Intensively Cultured Forests, J.A. Mattson, 3:31-38 (No. 6487).

A Low Cost Way to Recover Logging Residues, C.C. Hassler, S.A. Sinclair, and C.R. Blinn, 3:19-25 (No. 6462).

The Mechanics of Auger Cutters for Wood, J.A. Mattson, 2:31-38 (No. 6451).

A Method for Estimating the Multi-Product Value of Hardwood Timber Stands, C.R. Blinn, S.A. Sinclair, and A.R. Ek, 3:49-54 (No. 6485).

Moisture Content of Beetle-Killed Southern Pine Timber in Eastern Texas, D.W. Patterson, W.K. Murphey, and J.G. Massey, 1:67-68 (No. 6469).

Productivity and Costs of the Timberjack 30 Feller Buncher, B.L. Lanford, 1:62-66 (No. 6349).

Simulated Effects of Productivity Rates, Input Costs, and Stand Volumes on Harvesting Costs, F.W. Cubbage, 2:50-56 (No. 6461).

Stem Characteristic Changes Affect Long-Term Planning for Timber Resources Utilization, P.F. Ffolliott, W.O. Rasmussen, and G.J. Gottfried, 2:57-60 (No. 6476).

Wood Properties of Immature Ponderosa Pine After Thinning, D.C. Markstrom, H.E. Troxell, and C.E. Boldt, 4:33-36 (No. 6503).

Wood Utilization Potential of Beetle-Killed Lodgepole Pine for Solid Wood Products, R.L. Lemaster, H.E. Troxell, and G.R. Sampson, 9:64-68 (No. 6497).

Work Physiology Evaluation of Southern Forest Harvesting Tasks, L.A. Smith, G.D. Wilson, and D.L. Sirois, 9:38-44 (No. 6548).

PRODUCTS DIVISION

Bark & Residues

Cubic Log Scale Deductions in Dead Timber: An Empirical Approach, J.M. Cahill, 4:21-24 (No. 6494).

Effects of Outside Storage on the Energy Potential of Hardwood Particulate Fuels: Part I. Moisture Content and Temperature, M.S. White, M.L. Curtis, R.L. Sarles, and D.W. Green, 6:31-38 (No. 6521).

Effects of Outside Storage on the Energy Potential of Hardwood Particulate Fuels: Part II. Higher and Net Heating Values, M.S. White, M.L. Curtis, R.L. Sarles, and D.W. Green, 11/12:61-65 (No. 6522).

A Low Cost Way to Recover Logging Residues, C.C. Hassler, S.A. Sinclair, and C.R. Blinn, 3:19-25 (No. 6462).

Lumber Grade Yields From Spruce Budworm Damaged Balsam Fir, R.L. Govett, S.A. Sinclair, and J.L. Bowyer, 5:46-50 (No. 6498).

Moisture Changes in Oak and Hickory Fuel Chips on Roofed and Unroofed Louisiana Air-Drying Grounds as Affected by Pile Depth and Turning of Chips, P. Koch, 6:59-61 (No. 6533).

Moisture Content of Beetle-Killed Southern Pine Timber in Eastern Texas, D.W. Patterson, W.K. Murphey, and J.G. Massey, 1:67-68 (No. 6469).

Strength and Stiffness of Clear Douglas-fir Exposed to the Mount St. Helens Volcanic Eruption, H. Resch, J.W. Johnson, and B.A. Bendtsen, 7/8:52-56 (No. 6484).

Wood-Fired Steam Production--A Case Study, F-B. Lin, 7/8:63-69 (No. 6526).

Wood Utilization Potential of Beetle-Killed Lodgepole Pine for Solid Wood Products, R.L. Lemaster, H.E. Troxell, and G.R. Sampson, 9:64-68 (No. 6497).

Construction Plywood

Performance Tests on the Powered Back-Up Roll, J. Edens, 1:53-61 (No. 6459).

Decorative Veneers & Plywood

Cost Comparison of Two Processes for Laminating Thick Veneer, S.P. Loehnertz, 11/12:57-60 (No. 6563).

Drying Sweetgum Veneer With Various Combinations of Impinging Hot Air and Microwave Energy, J.R. Olson and D.G. Arganbright, 5:51-56 (No. 6303).

Formaldehyde Emission From Particleboard and Plywood Paneling: Measurement, Mechanism, and Product Standards, G.E. Myers, 5:27-37 (No. 6492).

Gluability of Platen-Dried Veneer of Douglas-fir, M.D. Sandoe, J.D. Wellons, R.J. Parker, and R. Jokerst, 7/8:57-62 (No. 6455).

Parallel-Laminated Veneer: Processing and Performance Research Review, T.L. Laufenberg, 9:21-28 (No. 6549).

Properties of 1/2-Inch Composite Plywood With Southern Yellow Pine Veneer Faces and Unidirectionally Oriented Southern Oaks Strand Core, E.J. Biblis and F. Mansalousis, 2:43-49 (No. 6447).

Proportion of Northern Red Oak Veneer Logs Processed Into Veneer and Byproducts in a Half-Round Slicing Operation, E.D. Rast, 11/12:54-56 (No. 6577).

Surface Roughness of Wood-Based Panels After Aging, B. A-L. Ostman, 7/8:35-42 (No. 6457).

Thickness Loss in Hot-Pressed Plywood, J.D. Wellons, R.L. Krahmer, M.D. Sandoe, and R.W. Jokerst, 1:27-34 (No. 6436).

Veneer Recovery From Live and Dead Lodgepole Pine, T.A. Snellgrove and S. Ernst, 6:21-26 (No. 6537).

Furniture, Millwork, & Allied Products

A Financial Analysis of Furniture Parts From Short Bolts, H.A. Huber, H.N. Rosen, H.A. Stewart, and S.B. Harsh, 9:55-58 (No. 6433).

Hardboard & Insulation Board

Effect of Hardboard Process Variables on Fiberbonding, O. Suchsland, G.E. Woodson, and C.W. McMillin, 4:58-64 (No. 6504).

Effect of Shives Content on Hardboard Properties, Y. DeXin and B. Ostman, 3:26-30 (No. 6479).

Hardboard Stiffness and Tensile Strength Over a Moisture and Temperature Range Simulating Exterior Use, E.L. Back and B. A-L. Ostman, 6:62-68 (No. 6519).

On the Measurement of Fiber Orientation in Fiberboard, O. Suchsland and C.W. McMillin, 10:39-42 (No. 6546).

Properties of Hardboards Made From Tropical Hardwoods and Aspen Chips Before and After Simulated Outdoor Storage, G.C. Myers, 2:39-42 (No. 6439).

Relationship of Fiber Preparation and Characteristics to Performance of Medium-Density Hardboards, G.C. Myers, 10:43-51 (No. 6518).

Hardwood Lumber

Bacterial Oak: Drying Problems, J.C. Ward and D.A. Groom, 10:57-65 (No. 6427).

Economics of Manufacturing Structural Lumber From Hardwoods Using the Saw-Dry-Rip (SDR) Concept, G.B. Harpole, 6:39-42 (No. 6500).

Effect of Gang-Ripping Width on CIF Yields From No. 2 Common Oak Lumber, C.J. Gatchell, R.B. Anderson, and P.A. Araman, 6:43-48 (No. 6539).

Effect of High-Temperature Drying on Bending Strength of Yellow-poplar 2 by 4's, C.C. Gerhards, 2:61-67 (No. 6465).

Field Trials of Chemicals to Control Sapstain and Mold on Yellow-poplar and Southern Yellow Pine Lumber, D.L. Cassens and W.E. Eslyn, 10:52-56 (No. 6568).

Manufacture of Quality Yellow-poplar Studs Using the Saw-Dry-Rip Concept, R.R. Maeglin and R.S. Boone, 3:10-18 (No. 6477).

Mechanical Properties of Conventionally Kiln-Dried and Pressure Steam-Dried Yellow-poplar and Red Oak, H.N. Rosen and S.E. Laurie, 1:50-52 (No. 6468).

Performance of a Thin Circular Headsaw Cutting Hardwoods, D.G. Cuppett, 9:33-35 (No. 6556).

Relationship of Bending Strength to Stiffness of Yellow-poplar 2 by 4's, C.B. Koch, 6:17-20 (No. 6248).

Laminated Wood, Components, & Engineered Structures

Cost Comparison of Two Processes for Laminating Thick Veneer, S.P. Loehnertz, 11/12:57-60 (No. 6563).

Influence of Flange Quality on the Load-Carrying Capacity of Composite Webbed I-Beam in Flexure, M. Samson, 1:38-42 (No. 6453).

Parallel-Laminated Veneer: Processing and Performance Research Review, T.L. Laufenberg, 9:21-28 (No. 6549).

Preventing Decay in Exposed Beams, W.A. Dost, 10:69-72 (No. 6575).

Ultimate Strength of Structural Particleboard Diaphragms, G.H. Atherton, 5:22-26 (No. 6501).

Particleboard & Molded Products

Assessment of the 2-Hour Desiccator Test for Formaldehyde Release From Particleboard, J. Rybicky, K. Horst, and S.M. Kambanis, 9:50-54 (No. 6527).

Bottomland Hardwoods for Structural Flakeboards, E.W. Price and C-Y. Hse, 11/12:33-40 (No. 6538).

Cutting Forces and Surface and Flake Quality From Face-Milling Combinations, H.A. Stewart, 7/8:27-32 (No. 6396).

Effects of Accelerated Aging Tests on Some Bending Properties of Hardwood Composite Panels, P. Chow and J.J. Janowiak, 2:14-20 (No. 6460).

Formaldehyde Emission From Particleboard and Plywood Paneling: Measurement, Mechanism, and Product Standards, G.E. Myers, 5:27-37 (No. 6492).

The Minnesota Shear Test, H.J. Hall and J.G. Haygreen, 9:29-32 (No. 6559).

Properties of 1/2-Inch Composite Plywood With Southern Yellow Pine Veneer Faces and Unidirectionally Oriented Southern Oaks Strand Core, E.J. Biblis and F. Mansalousis, 2:43-49 (No. 6447).

Surface Roughness of Wood-Based Panels After Aging, B. A-L. Ostman, 7/8:35-42 (No. 6457).

Ultimate Strength of Structural Particleboard Diaphragms, G.H. Atherton, 5:22-26 (No. 6501).

Pulp & Paper

Derived Demand of Factors of Production in the Pulp and Paper Industry, F. Sherif, 1:45-49 (No. 6306).

Residential & Commercial Buildings

Comparing In-Place Costs of Wood and Masonry Foundations, H. Spelter, 9:45-49 (No. 6547).

Influence of Flange Quality on the Load-Carrying Capacity of Composite Webbed I-Beams in Flexure, M. Samson, 1:38-42 (No. 6453).

Longitudinal Moisture Response in Truss Lumber--A Potential Cause of Ceiling-Partition or Floor-Partition Separation, D.H. Percival and S.K. Suddarth, 11/12:19-28 (No. 6557).

Serviceability of Douglas-fir Shakes After 22 Years on a Roof in Western Oregon, D.J. Miller, 11/12:66-68 (No. 6561).

Softwood Lumber

Chemical Brown Staining of Douglas-fir Sapwood, D.J. Miller, D.M. Knutson, and R.D. Tocher, 4:44-48 (No. 6481).

Compression Perrendicular to the Grain in Dry Douglas-fir and Hem-fir, J.W. Johnson, 3:55-63 (No. 6474).

Control of Brown Stain in Eastern White Pine With Reducing Agents, M.A. Hulme and J.F. Thomas, 9:17-20 (No. 6532).

Decay Resistance of Alaska-cedar, T.C. Scheffer, 1:25-26 (No. 6241).

Edge-Gluing Unseasoned Spruce-Pine-Fir Lumber Using a Preheating Method, G.E. Troughton and R.C. Casilla, 5:38-44 (No. 6496).

Effect of Delay Between Treatment and Drying on Toughness of CCA-Treated Southern Pine, J.E. Winandy, B.A. Bendtsen, and R.S. Boone, 6:53-58 (No. 6520).

Field Trials of Chemicals to Control Sapstain and Mold on Yellow-Poplar and Southern Yellow Pine Lumber, D.L. Cassens and W.E. Eslyn, 10:52-56 (No. 6568).

Laboratory Evaluation of Selected Fungicides for Control of Sapstain and Mold on Southern Pine Lumber, W.E. Eslyn and D.L. Cassens, 4:65-68 (No. 6510).

Lumber Grade Yields From Spruce Budworm-Damaged Balsam Fir, R.L. Govett, S.A. Sinclair, and J.L. Bowyer, 5:46-50 (No. 6498).

Natural Decay Resistance of the Heartwood of Coast Redwood Sequoia Sempervirens (D. Don) Endl., J.W. Clark and T.C. Scheffer, 5:15-20 (No. 6240).

Pressure Steam Drying of Lumber, H.N. Rosen, R.E. Bodkin, and K.D. Gaddis, 1:17-24 (No. 6450).

Relationship Between Early Decay and Radial Compression Strength of Douglas-fir, S.M. Smith and R.D. Graham, 6:49-52 (No. 6514).

SPSM--A Southern Pine Sawmill Model, F.G. Wagner, Jr., and F.W. Taylor, 4:37-43 (No. 6505).

Toughness of Healthy and Spruce Budworm-Killed Balsam Fir, S.A. Sinclair and D.P. Barnes, 7/8:24-26 (No. 6515).

Wood Utilization Potential of Beetle-Killed Lodgepole Pine for Solid Wood Products, R.L. Lemaster, H.E. Troxell, and G.R. Sampson, 9:64-68 (No. 6497).

Treated Wood Products

Biodeterioration and Strength Reductions in Preservative Treated Aspen Waferboard, E.L. Schmidt, H.J. Hall, R.O. Gertjejansen, C.G. Carll, and R.C. DeGroot, 11/12:45-53 (No. 6570).

Control of Brown Stain in Eastern White Pine With Reducing Agents, M.A. Hulme and J.F. Thomas, 9:17-20 (No. 6532).

Effect of Accelerated Fixation on Decay of CCA-Treated Wood, A.F. Preston, and P.A. McKaig, 11/12:41-44 (No. 6553).

Effect of Delay Between Treatment and Drying on Toughness of CCA-Treated Southern Pine, J.E. Winandy, B.A. Bendtsen, and R.S. Boone, 6:53-58 (No. 6520).

Field Trials of Chemicals to Control Sapstain and Mold on Yellow-poplar and Southern Yellow Pine Lumber, D.L. Cassens and W.E. Eslyn, 10:52-56 (No. 6568).

Field Trials With Ammoniacal Copper Borate Wood Preservative, B.R. Johnson, 9:59-63 (No. 6551).

Hardness of Douglas-fir and Ponderosa Pine Treated With ACA, CCA, and Penta-Petroleum, J.D. Lew and W.A. Dost, 7/8:17-18 (No. 6524).

Laboratory Evaluation of Selected Fungicides for Control of Sapstain and Mold on Southern Pine Lumber, W.E. Eslyn and D.L. Cassens, 4:65-68 (No. 6510).

Pressure Steam Drying of Lumber, H.N. Rosen, R.E. Bodkin, and K.D. Gaddis, 1:17-24 (No. 6450).

Preventing Decay in Exposed Beams, W.A. Dost, 10:69-72 (No. 6575).

A Slide-Hammer for Pulling Plugs in Fumigated Transmission Poles, G.M. Cantara and R.D. Graham, 5:45 (No. 6543).

Tropical Woods

Factors Preventing Wider Commercialization of Nigerian Trees, E.B. Lucas, 5:64-68 (No. 6445).

AUTHOR INDEX

A

Anderson, R.B., see Gatchell, C.J.
Araman, P.A., see Gatchell, C.J.
Arganbright, D.G., see Olson, J.R.
Arola, R.A., S.A. Winsauer, R.C. Radcliffe, and M.R. Smith, Chunkwood Production: A New Concept, 7/8:43-51 (No. 6508).
Atherton, G.H., Ultimate Strength of Structural Particleboard Diaphragms, 5:22-26 (No. 6501).

B

Back, E.L., and B. A-L. Ostman, Hardboard Stiffness and Tensile Strength Over a Moisture and Temperature Range Simulating Exterior Use, 6:62-68 (No. 6519).
Ball, J.A., Forest Products in the Future: The Eighties as Prologue, 10:9-13 (No. 6627).
Barnes, D.P., see Sinclair, S.A.
Beal, R.H., see Bultman, J.D.
Bechtel, F.K., Proof Test Load Value Determination for Maximum Economic Return, 10:30-38 (No. 6470).
Beesley, J., J.W. Creffield, and I.W. Saunders, An Australian Test for Decay in Painted Timbers Exposed to the Weather, 5:57-63 (No. 6472).
Bendtsen, B.A., see Resch, H.
Bendtsen, B.A., see Winandy, J.E.
Biblis, E.J., and F. Mangalousis, Properties of 1/2-Inch Composite Plywood With Southern Yellow Pine Veneer Faces and Unidirectionally Oriented Southern Oaks Strand Core, 2:43-49 (No. 6447).
Blinn, C.R., S.A. Sinclair, and A.R. Ek, A Method for Estimating the Multi-Product Value of Hardwood Timber Stands, 3:49-54 (No. 6485).
Blinn, C.R., see Hassler, C.C.
Bodkin, R.E., see Rosen, H.N.
Boldt, C.E., see Markstrom, D.C.
Boone, R.S., see Maeglin, R.R.
Boone, R.S., see Winandy, J.E.
Bowyer, J.L., see Govett, R.L.
Bultman, J.D., R.H. Beal, J.B. Huffman, and K.K. Parrish, An Investigation of the Natural Resistance of Melaleuca quinquenervia to Tropical and Terrestrial Wood-Destroying Organisms, 3:39-43 (No. 6471).

C

Cahill, J.M., Cubic Log Scale Deductions in Dead Timber: An Empirical Approach, 4:21-24 (No. 6494).
Cantara, G.M., and R.D. Graham, A Slide-Hammer for Pulling Plugs in Fumigated Transmission Poles, 5:45 (No. 6543).
Carll, C.G., see Schmidt, E.L.
Casilla, R.C., see Troughton, G.E.
Cassens, D.L., and W.E. Eslyn, Field Trials of Chemicals to Control Sapstain and Mold on Yellow-poplar and Southern Yellow Pine Lumber, 10:52-56 (No. 6568).
Cassens, D.L., see Eslyn, W.E.
Chow, P., and J.J. Janowiak, Effects of Accelerated Aging Tests on Some Bending Properties of Hardwood Composite Panels, 2:14-20 (No. 6460).
Clark, J.W., and T.C. Scheffer, Natural Decay Resistance of the Heartwood of Coast Redwood Sequoia Sempervirens (D. Don) Endl., 5:15-20 (No. 6240).
Creffield, J.W., see Beesley, J.
Cubbage, F.W., Simulated Effects of Productivity Rates, Input Costs, and Stand Volumes on Harvesting Costs, 2:50-56 (No. 6461).
Cuppett, D.G., Performance of a Thin Circular Headsaw Cutting Hardwoods, 9:33-35 (No. 6556).
Curtis, M.L., see White, M.S.
Curtis, M.L., see White, M.S.

D

Darr, D.R., How Export Promotion Programs Influence Trade, 4:15-20 (No. 6480).
Dean, M.A., and A.J. Kass, Predicting the Bending Strength of Ladder Rail Stock, 9:9-16 (No. 6525).
DeGroot, R.C., see Schmidt, E.L.
DeXin, Y., and B. Ostman, Effect of Shives Content on Hardboard Properties, 3:26-30 (No. 6479).
Dost, W.A., Preventing Decay in Exposed Beams, 10:69-72 (No. 6575).
Dost, W.A., see Lew, J.D.

E

Edens, J., Performance Tests on the Powered Back-Up Roll, 1:53-61 (No. 6459).

Einspahr, D.W., and M.L. Harder, Wood/Bark Adhesion Measurements Assist in Drum Debarker Development, 5:21 (No. 6552).

Ek, A.R., see Blinn, C.R.

Ernst, S., see Snellgrove, T.A.

Eslyn, W.E., Decay in Mine Timbers. Part I. Sampling Procedures and Conditions and Descriptions of Samples, 6:27-30 (No. 6534).

Eslyn, W.E., and F.F. Lombard, Decay in Mine Timbers. Part II. Basidiomycetes Associated With Decay of Coal Mine Timbers, 7/8:19-23 (No. 6535).

Eslyn, W.E., and D.L. Cassens, Laboratory Evaluation of Selected Fungicides for Control of Sapstain and Mold on Southern Pine Lumber, 4:65-68 (No. 6510).

Eslyn, W.E., see Cassens, D.L.

F

Ffolliott, P.F., W.O. Rasmussen, and G.J. Gottfried, Stem Characteristic Changes Affect Long-Term Planning for Timber Resources Utilization, 2:57-60 (No. 6476).

G

Gaddis, K.D., see Rosen, H.N.

Gatchell, C.J., R.B. Anderson, and P.A. Araman, Effect of Gang-Ripping Width on CIF Yields From No. 2 Common Oak Lumber, 6:43-48 (No. 6539).

Geisling, K.L., see Meyer, B.

Gerhards, C.C., Effect of High-Temperature Drying on Bending Strength of Yellow-poplar 2 by 4's, 2:61-67 (No. 6465).

Gertjejansen, R.O., see Schmidt, E.L.

Gillespie, R.H., see Kelley, S.S.

Goetzl, A., and S. Tatum, Wood Energy Use in the Lumber and Wood Products Industry, 3:44-48 (No. 6511).

Gottfried, G.J., see Ffolliott, P.F.

Govett, R.L., S.A. Sinclair, and J.L. Bowyer, Lumber Grade Yields From Spruce Budworm-Damaged Balsam Fir, 5:46-50 (No. 6498).

Graham, R.D., see Cantara, G.M.

Graham, R.D., see Smith, S.M.

Green, D.W., see White, M.S.

Green, D.W., see White, M.S.

Groom, D.A., see Ward, J.C.

H

Hall, H.J., and J.G. Haygreen, The Minnesota Shear Test, 9:29-32 (No. 6559).

Hall, H.J., see Lebens, G.A.

Hall, H.J., see Schmidt, E.L.

Harder, M.L., see Einspahr, D.W.

Harpole, G.B., Economics of Manufacturing Structural Lumber From Hardwoods Using the Saw-Dry-Rip (SDR) Concept, 6:39-42 (No. 6500).

Harsh, S.B., see Huber, H.A.

Hassler, C.C., S.A. Sinclair, and C.R. Blinn, A Low Cost Way to Recover Logging Residues, 3:19-25 (No. 6462).

Haygreen, J.G., see Hall, H.J.

Hines, G.S., C-Y. Liu, D.B. Webster, and D.L. Sirois, Features of a Skidding Module in a Timber Harvesting Computer Simulation Model, 7/8:11-16 (No. 6507).

Horst, K., see Rybicky, J.

Hse, C-Y., see Price, E.W.

Huber, H.A., H.N. Rosen, H.A. Stewart, and S.B. Harsh, A Financial Analysis of Furniture Parts From Short Bolts, 9:55-58 (No. 6433).

Huffman, J.B., see Bultman, J.D.

Hulme, M.A., and J.F. Thomas, Control of Brown Stain in Eastern White Pine With Reducing Agents, 9:17-20 (No. 6532).

J

Janowiak, J.J., see Chow, P.

Johnson, B.R., Field Trials With Ammoniacal Copper Borate Wood Preservative, 9:59-63 (No. 6551).

Johnson, J.W., Compression Perpendicular to the Grain in Dry Douglas-fir and Hem-fir, 3:55-63 (No. 6474).

Johnson, J.W., see Resch, H.

Jokerst, R., see Sandoe, M.D.

Jokerst, R.W., see Wellons, J.D.

K

Kambanis, S.M., see Rybicky, J.

Kass, A.J., see Dean, M.A.

Kelley, S.S., R.A. Young, R.M. Rannon, and R. H. Gillespie, Bond Formation by Wood Surface Reactions: Part III--Parameters Affecting the Bond Strength of Solid Wood Panels, 2:21-28 (No. 6463).

Kellogg, L.D., Handling the Small Tree Resource With Cable Systems, 4:25-32 (No. 6509).

Knutson, D.M., see Miller, D.J.

Koch, C.B., Relationship of Bending Strength to Stiffness of Yellow-poplar 2 by 4's, 6:17-20 (No. 6248).

Koch, P., Moisture Changes in Oak and Hickory Fuel Chips on Roofed and Unroofed Louisiana Air-Drying Grounds as Affected by Pile Depth and Turning of Chips, 6:59-61 (No. 6533).

Koshlar, K., see Meyer, B.

Krahmer, R.L., see Wellons, J.D.

L

Lanford, B.L., Productivity and Costs of the Timberjack 30 Feller Buncher, 1:62-66 (No. 6349).

Laufenberg, T.L., Parallel-Laminated Veneer: Processing and Performance Research Review, 9:21-28 (No. 6549).

Laurie, S.E., see Rosen, H.N.

Lebens, G.A., and H.J. Hall, Hot Melt Adhesive Applicator Speeds Gluing of Internal Bond Test Specimens, 7/8:33-34 (No. 6560).

Lemaster, R.L., H.E. Troxell, and G.R. Sampson, Wood Utilization Potential of Beetle-Killed Lodgepole Pine for Solid Wood Products, 9:64-68 (No. 6497).

Lew, J.D., and W.A. Dost, Hardness of Douglas-fir and Ponderosa Pine Treated With ACA, CCA, and Penta-Petroleum, 7/8:17-18 (No. 6524).
Lin, F-B., Wood-Fired Steam Production--A Case Study, 7/8:63-69 (No. 6526).
Liu, C-Y., see Hines, G.S.
Loehnertz, S.P., Cost Comparison of Two Processes for Laminating Thick Veneer, 11/12:57-60 (No. 6563).
Lombard, F.F., see Eslyn, W.E.
Lucas, E.B., Factors Preventing Wider Commercialization of Nigerian Trees, 5:64-68 (No. 6445).

M

Maeglin, R.R., and R.S. Boone, Manufacture of Quality Yellow-poplar Studs Using the Saw-Dry-Rip Concept, 3:10-18 (No. 6477).
Mangalousis, F., see Biblis, E.J.
Markstrom, D.C., H.E. Troxell, and C.E. Boldt, Wood Properties of Immature Ponderosa Pine After Thinning, 4:33-36 (No. 6503).
Marsinko, A.P.C., and T.E. Wooten, Pickup Trucks as Units for Measuring Firewood, 1:43-44 (No. 6482).
Massey, J.G., see Patterson, D.W.
Mattson, J.A., Harvesting Developments for Short Rotation Intensively Cultured Forests, 3:31-38 (No. 6487).
Mattson, J.A., The Mechanics of Auger Cutters for Wood, 2:31-38 (No. 6451).
McKaig, P.A., see Preston, A.F.
McMillin, C.W., see Suchsland, O.
McMillin, C.W., see Suchsland, O.
Meyer, B., K. Koshlap, K.L. Geisling, and R.R. Miksch, Comparison of Wet and Dry Desiccator Test Methods for Formaldehyde Emission From UF-Bonded Wood Products, 1:35-37 (No. 6466).
Miksch, R.R., see Meyer, B.
Miller, D.J., Serviceability of Douglas-fir Shakes After 22 Years on a Roof in Western Oregon, 11/12:66-68 (No. 6561).
Miller, D.J., D.M. Knutson, and R.D. Tocher, Chemical Brown Staining of Douglas-fir Sapwood, 4:44-48 (No. 6481).
Murphey, W.K., see Patterson, D.W.
Myers, G.C., Properties of Hardboards Made From Tropical Hardwoods and Aspen Chips Before and After Simulated Outdoor Storage, 2:39-42 (No. 6439).
Myers, G.C., Relationship of Fiber Preparation and Characteristics to Performance of Medium-Density Hardboards, 10:43-51 (No. 6518).
Myers, G.E., Formaldehyde Emission From Particleboard and Plywood Paneling: Measurement, Mechanism, and Product Standards, 5:27-37 (No. 6492).
Myers, G.E., Use of Acid Scavengers to Improve Durability of Acid-Catalyzed Adhesive Wood Bonds, 4:49-57 (No. 6464).

O

Olson, J.R., and D.G. Arganbright, Drying Sweetgum Veneer With Various Combinations of Impinging Hot Air and Microwave Energy, 5:51-56 (No. 6303).
Ostman, B. A-L., Surface Roughness of Wood-Based Panels After Aging, 7/8:35-42 (No. 6457).
Ostman, B. A-L., see Back, E.L.
Ostman, B., see DeXin, Y.

P

Padgett, M.L., see Webster, D.B.
Parker, R.J., see Sandoe, M.D.
Parrish, K.K., see Bultman, J.D.
Patterson, D.W., W.K. Murphey, and J.G. Massey, Moisture Content of Beetle-Killed Southern Pine Timber in Eastern Texas, 1:67-68 (No. 6469).
Percival, D.H., and S.K. Suddarth, Longitudinal Moisture Response in Truss Lumber--A Potential Cause of Ceiling-Partition or Floor-Partition Separation, 11/12:19-28 (No. 6557).
Preston, A.F., and P.A. McKaig, Effect of Accelerated Fixation on Decay of CCA-Treated Wood, 11/12:41-44 (No. 6553).
Price, E.W., and C-Y. Hse, Bottomland Hardwoods for Structural Flakeboards, 11/12:33-40 (No. 6538).

R

Radcliffe, R.C., see Arola, R.A.
Rammon, R.M., see Kelley, S.S.
Rasmussen, W.O., see Ffolliott, P.F.
Rast, E.D., Proportion of Northern Red Oak Veneer Logs Processed Into Veneer and Byproducts in a Half-Round Slicing Operation, 11/12:54-56 (No. 6577).
Resch, H., J.W. Johnson, and B.A. Bendtsen, Strength and Stiffness of Clear Douglas-fir Exposed to the Mount St. Helens Volcanic Eruption, 7/8:52-56 (No. 6468).
Rosen, H.N., R.E. Bodkin, and K.D. Gaddis, Pressure Steam Drying of Lumber, 1:17-24 (No. 6450).
Rosen, H.N., and S.E. Laurie, Mechanical Properties of Conventionally Kiln-Dried and Pressure Steam-Dried Yellow-poplar and Red Oak, 1:50-52 (No. 6468).
Rosen, H.N., see Huber, H.A.
Rybicky, J., K. Horst, and S.M. Kambanis, Assessment of the 2-Hour Desiccator Test for Formaldehyde Release From Particleboard, 9:50-54 (No. 6527).

S

Sampson, G.R., see Lemaster, R.L.
Samson, M., Influence of Flange Quality on the Load-Carrying Capacity of Composite Webbed I-Beams in Flexure, 1:38-42 (No. 6453).
Sandoe, M.D., J.D. Wellons, R.J. Parker, and R. Jokerst, Gluability of Platen-Dried Veneer of Douglas-fir, 7/8:57-62 (No. 6455).
Sandoe, M.D., see Wellons, J.D.
Sarles, R.L., see White, M.S.
Sarles, R.L., see White, M.S.
Saunders, I.W., see Beesley, J.
Scheffer, T.C., Decay Resistance of Alaska-cedar, 1:25-26 (No. 6241).

Scheffer, T.C., see Clark, J.W.
Schmidt, E.L., H.J. Hall, R.O. Gertjejansen, C.G. Carll, and R.C. DeGroot, Biodeterioration and Strength Reductions in Preservative Treated Aspen Waferboard, 11/12:45-53 (No. 6570).
Sherif, F., Derived Demand of Factors of Production in the Pulp and Paper Industry, 1:45-49 (No. 6306).
Sinclair, S.A., and D.P. Barnes, Toughness of Healthy and Spruce Budworm-Killed Balsam Fir, 7/8:24-26 (No. 6515).
Sinclair, S.A., see Blinn, C.R.
Sinclair, S.A., see Govett, R.L.
Sinclair, S.A., see Hassler, C.C.
Sirois, D.L., see Hines, G.S.
Sirois, D.L., see Smith, L.A.
Sirois, D.L., see Webster, D.B.
Smith, L.A., G.D. Wilson, and D.L. Sirois, Work Physiology Evaluation of Southern Forest Harvesting Tasks, 9:38-44 (No. 6548).
Smith, M.R., see Arola, R.A.
Smith, S.M., and R.D. Graham, Relationship Between Early Decay and Radial Compression Strength of Douglas-fir, 6:49-52 (No. 6514).
Snellgrove, T.A., and S. Ernst, Veneer Recovery From Live and Dead Lodgepole Pine, 6:21-26 (No. 6537).
Spelter, H., Comparing In-Place Costs of Wood and Masonry Foundations, 9:45-49 (No. 6547).
Stewart, H.A., Cutting Forces and Surface and Flake Quality From Face-Milling Combinations, 7/8:27-32 (No. 6396).
Stewart, H.A., see Huber, H.A.
Suchsland, O., and C.W. McMillin, On the Measurement of Fiber Orientation in Fiberboard, 10:39-42 (No. 6546).
Suchsland, O., G.E. Woodson, and C.W. McMillin, Effect of Hardboard Process Variables on Fiberbonding, 4:58-64 (No. 6504).
Suddarth, S.K., see Percival, D.H.

T

Tatum, S., see Goetzl, A.
Taylor, F.W., see Wagner, F.G., Jr.
Thomas, J.F., see Hulme, M.A.
Tocher, R.D., see Miller, D.J.
Troughton, G.E., and R.C. Casilla, Edge-Gluing Unseasoned Spruce-Pine-Fir Lumber Using a Preheating Method, 5:38-44 (No. 6496).
Troxell, H.E., see Lemaster, R.L.
Troxell, H.E., see Markstrom, D.C.

W

Wagner, F.G., Jr., and F.W. Taylor, SPSM--A Southern Pine Sawmill Model, 4:37-43 (No. 6505).
Wang, S-c., Screening Biomass Species for Methane Production in Florida: Description of a Research Program, 10:66-68 (No. 6523).
Wang, S.J., An Analytic Approach to Estimating the Increase in Lumber Recovery Due to Reduced Target Sizes and Saw Kerfs, 11/12:29-32 (No. 6564).
Ward, J.C., and D.A. Groom, Bacterial Oak: Drying Problems, 10:57-65 (No. 6427).
Webster, D.B., M.L. Padgett, and D.L. Sirois, Features of a Felling Module Using a Feller-Buncher in a Timber Harvesting Computer Simulation Model, 6:11-16 (No. 6506).
Webster, D.B., see Hines, G.S.
Wellons, J.D., R.L. Krahmer, M.D. Sandoe, and R.W. Jokerst, Thickness Loss in Hot-Pressed Plywood, 1:27-34 (No. 6436).
Wellons, J.D., see Sandoe, M.D.
White, M.S., M.L. Curtis, R.L. Sarles, and D.W. Green, Effects of Outside Storage on the Energy Potential of Hardwood Particulate Fuels: Part I. Moisture Content and Temperature, 6:31-38 (No. 6521).
White, M.S., M.L. Curtis, R.L. Sarles, and D.W. Green, Effects of Outside Storage on the Energy Potential of Hardwood Particulate Fuels: Part II. Higher and Net Heating Values, 11/12:61-65 (No. 6522).
Wilcox, W.W., Sensitivity of the "Pick Test" for Field Detection of Early Wood Decay, 2:29-30 (No. 6490).
Wilson, G.D., see Smith, L.A.
Winandy, J.E., B.A. Bendtsen, and R.S. Boone, Effect of Delay Between Treatment and Drying on Toughness of CCA-Treated Southern Pine, 6:53-58 (No. 6520).
Winsauer, S.A., see Arola, R.A.
Woodson, G.E., see Suchsland, O.

Y

Young, R.A., see Kelley, S.S.
Youngs, R.L., Forest Service Research--New Views of an Old Mission, 11/12:15-18 (No. 6623).